



# Z5615-BWL

HET Elongated Wall Hung EcoVantage® Flush Valve Toilet

TAG \_\_\_\_\_

## Architectural/Engineering Specification:

### Z5615-BWL

#### EcoVantage High Efficiency Toilet System

Vitreous China, 1.1 gpf [4.2 Lpf] or greater high efficiency wall hung toilet with siphon jet flushing action, elongated front rim with 1-1/2" top spud. Universal high efficiency toilet is designed to exceed industry standards with flush volumes of 1.1 gallons per flush.

### Z5615-BWL-AM

#### EcoVantage High Efficiency Toilet System

Vitreous China, 1.1 gpf [4.2 Lpf] or greater high efficiency wall hung toilet with siphon jet flushing action, ZurnSHIELD™ ceramic glaze and elongated front rim with 1-1/2" top spud. Universal high efficiency toilet is designed to exceed industry standards with flush volumes of 1.1 gallons per flush.

### Z5616-BWL

#### EcoVantage High Efficiency Toilet System

Vitreous China, 1.1 gpf [4.2 Lpf] or greater high efficiency wall hung toilet with siphon jet flushing action, ZurnSHIELD™ ceramic glaze and elongated front rim with integral bedpan lugs 1-1/2" top spud. Universal high efficiency toilet is designed to exceed industry standards with flush volumes of 1.1 gallons per flush..

## Product Features:

### Z5615 HET Series

- Zurn High Efficiency Toilets and paired performance flush valve systems are designed to exceed industry standards, while using as little as 1.1 gallons of water per flush.
- Universal high efficiency toilet can be specified with 1.1 gpf [4.2 Lgf], 1.28 gpf [4.8 Lpf], 1.6 gpf [6.0 Lpf] or dual flush valves.
- Vitreous china
- ZurnSHIELD™ ceramic glaze creates a permanent surface that protects the fixture by inhibiting the growth of stain and odor causing mold, mildew, and bacteria, thus reducing the amount of time, chemicals and water needed to clean the bowl.
- Elongated front rim
- 2-1/8" fully glazed trapway
- High efficiency siphon jet flush action
- Shipping Weight: 40 lbs.
- System MaP score of 1,000 grams at 1.28 gpf with Zurn Flush Valve
- Static weight load of 1,000 lbs\*  
\*Not intended for bariatric use

## Compliance and Certification:

- Complies with ASME A119.2 / CSA B45.1
- ADA Compliant



This product should be used with a WaterSense labeled counterpart with a compatible flush volume to ensure that the entire system meets the requirements for water efficiency and performance.



## Variant Options:

### Z5615-BWL

Z5615 Series Top spud toilet

### Z5615-BWL-AM

Z5615 Series top spud toilet with ZurnSHIELD™ glaze

### Z5616-BWL

Z5615 Series top spud toilet with Top Spud Toilet with integral bed pan lugs and ZurnSHIELD™ glaze

## Z5615-BWL Series

### Option:

-RF Retro-Fit Nut Kit for extending carrier studs from existing wall.

### Recommended Trim:

Z5955SS-EL Elongated, standard white, open front toilet seat less cover with stainless steel check hinge.

### Recommended Carrier:

Z1201 or Z1202 EZCarry™ 500 lbs load rated High Efficiency Carrier

NOTE: To ensure system performance:  
Minimum Running Water Pressure = 25 psi.

Architectural/Engineering Approval

The information contained in this document is subject to change without notice. Please contact Zurn for most up to date information.

### Rough-in dimensions/Overview dimensions

